

120/277 VAC tube solution

Replaces T8 & T12 tubes with direct 120/277 VAC connection

8FT LED Tube - Lifetime of 50,000 hours, 5 year Warranty

The Bramal LED tube solution for direct AC connection - Type B

Building on the patented BRAMAL LED multi-purpose tube, we have developed a low-cost AC tube solution for eliminating energyhungry ballasts and lowering the cost of commercial and industrial lighting. This new development remains consistent with the strict specification requirements of BRAMAL LED, with high quality, low power (40W), a 50,000-hour lifetime, familiar T8 form factor and only requiring a ballast bypass and no additional rewiring.

FEATURES OF THE BRAMAL LED AC TUBE SOLUTION

- SUITABLE for direct connection on alternating current (see installation instructions for details) (120-277VAC versions available see www.bramalled.com for more information)
- MINIMUM OPERATING TIME OF 50,000 HOURS.
- VISUAL ANGLE OF 180 DEGREES FOR FROSTED TUBE DLC Certified
- LIGHTS UP INSTANTLY NO MATTER THE CLIMATE: cold, hot or humid
- REDUCES ENERGY CONSUMPTION BY UP TO 50% compared to conventional fluorescent lamps
- PRODUCES LESS HEAT: ideal for applications in refrigerated or air-conditioned environments
- **PLASTIC AND ALUMINIUM construction**
- ENVIRONMENTALLY FRIENDLY: components are RoHS (do not contain lead mercury or cadmium), with zero persistent and volatile organic pollutants
- **AVAILABLE FORMATS: 8 FT**













CHARACTERISTICS - LED-T8-8FT-120/277V-40-XXXX-SP

MODEL : T8 LED 8FT		FROSTED TUBE
Energy Consumption		40W
Input Voltage		120 VAC – 277 VAC
Waterproof		IP22
Load Factor		>0.9
Light Efficiency (naked lamp)		
	4000K	120 lm/w
	5000K	120 lm/w
Luminous Power (naked lamp)	4000K	4800 lm
	5000K	4800 lm
Color Rendering Index (IRC)		
	4000K	>85
	5000K	>85
Standard Color Temperatures		4000K / 5000K
Light Flow Maintenance L ₇₀		97 %
Operating Ambient Temperature		20°C (-25 to + 60°C)
Length (FACE TO FACE)		2400mm
Lifetime		50,000 hours
Warranty		5 years
Standard End cap		FA8, R17D (not DLC)
Certifications		<u>cETLus</u> <u>DLC</u>

For more information, please send an email to info@Bramalled.com or call at 450-763-1443. To place an order, please contact PO@Bramalled.com.

Please note that the values of the datasheet have a margin of +/-3%.





